

SPECIFICATION

IRBE

SUBMINIATURE POWER RELAY

CONTACT DATA

Contact arrangement	1A	1C
Contact resistance	100mΩ (at 1A 6VDC)	
Contact material	Silver Alloy	
Contact rating (Res. load)	16A 250VAC TV-5A@ 125VAC	
Minimum Load	100mA 5VDC	
Max. switching voltage	440VAC/125VDC	
Max. switching current	16A	
Max. switching power	4000VA	
Mechanical endurance	1 x 10 ⁷ ops	
Electrical endurance	1 x 10 ⁵ ops	

CHARACTERISTICS

Insulation resistance		100MΩ (at 500VDC)
Dielectric strength	Between coil & contacts	5000VAC 1min
	Between open contacts	1000VAC 1min
Operate time (at nomi. Volt.)		15ms max.
Release time (at nomi. Volt.)		8ms max.
Shock resistance	Functional	10G
	Destructive	100G
Vibration resistance		10Hz to 55Hz 1.5mm DA
Humidity		40 ~ 85%
Ambient temperature		-40°C to 85°C
Termination		PCB
Unit weight		Approx. 14g
Max. Switching frequency	Mechanical	18,000 ops/hr
	Electrical	1,200 ops/hr

Notes : 1) The data shown above are initial values.

COIL

Coil power	0.4W
------------	------

COIL DATA

at 23°C
(0.4W)

Nominal Voltage VDC	Pick-up Voltage VDC	Drop-out Voltage VDC	Rated Current (mA)	Coil Resistance Ω
5	3.5	0.5	80	62 x (1±10%)
6	4.2	0.6	66.7	90 x (1±10%)
9	6.3	0.9	44.6	202 x (1±10%)
12	8.4	1.2	33.3	360 x (1±10%)
18	12.6	1.8	22.2	810 x (1±10%)
24	16.8	2.4	16.7	1440 x (1±10%)
48	33.6	4.8	8.3	5760 x (1±10%)


ORDERING INFORMATION


Type		IRBE	-1C	D12	S
Contact Form	1A : 1 Form A , 1C : 1 Form C				
Coil Voltage	5, 6, 9, 12, 18, 24, 48 VDC				
Construction	S : Sealed Type				

SAFETY APPROVAL RATINGS


UL&CUL	16A 250VAC TV-5A@ 125VAC	5 to 48VDC	
--------	-----------------------------	------------	--

CHARACTERISTIC CURVES








PCB Layout



Wiring Diagram



1 Form C



1 Form A